

Pump 40-250								
بمپ های سانتریفیوژ روغن داغ								
ردیف	توان مورد نیاز کیلو وات	بازدهی متر مکعب بر ثانیه	ارتفاع متر	قطر پروانه میلیمتر	دور در دقیقه	دهانه مکش اینچ	دهانه دهش اینچ	وزن کیلوگرم
Hot Oil Sentrifuge Pumps								
row	Power Kw	Capacity m ³ /s	hight m	impeller mm	R.P.M	Suction inch	Discharge inch	weight Kg
1	3	4	22	264	1450	2 1/2"	1 1/4"	56
2	3	4	18.6	245				
3	1.5	4	15	223				
4	1.1	4	12.4	205				
5	3	12	21.3	264				
6	3	12	17.8	245				
7	1.5	12	14.2	223				
8	1.1	12	11.5	205				
9	3	20	19.9	264				
10	3	20	16.2	245				
11	1.5	20	12.5	223				
12	1.1	20	9.5	205				
13	3	28	17	264	2900	2 1/2"	1 1/4"	56
14	3	28	13	245				
15	3	32	15.3	264				
16	30	10	91.6	264				
17	22	10	81.6	250				
18	18.5	10	72.6	238				
19	15	10	64	225				
20	11	10	55.6	210				
21	30	30	88.3	264				
22	22	30	77.6	250				
23	18.5	30	68.6	238				
24	15	30	60	225				
25	11	30	51	210				
26	30	40	84.3	264				
27	22	40	73	250				
28	18.5	40	64.6	238				
29	15	40	55.6	225				
30	11	40	44.6	210				
31	30	50	78	264				
32	22	50	66.6	250				
33	18.5	50	58	238				
34	15	50	48.3	225				
35	30	60	69	264				