

CPm



Application Limits

- Suction head up to 7m
- Liquid temperature up to +40°C
- Ambient temperature up to +40°C
- Max. Working pressure: 6bar
- Voltage fluctuation should not exceed 10% of rated value.
- pH: 6.5 to 8.5

Advantages & Features

- Single suction centrifugal pump, with high efficiency
- Copper impeller, stable performance
- High head, small flow rate

Performance Data

Model	Power		Max. Flow (m ³ /h)	Max. Head (m)	Head Range (m)	Max. Suction (m)	Packing Dim. L×W×H(mm)	G.W (kg)	20'Loading Qty. (pcs)	Inlet	Outlet
	kW	HP									
CPm370	0.37	0.5	6	22	22~8	7	300×205×270	9	1672	G1	G1
CPm550	0.55	0.75	6.6	26	26~11	7	330×225×285	12	1456	G1	G1
CPm750	0.75	1	7.2	32	32~14	7	330×230×300	14	1225	G1	G1
CPm170	1.1	1.5	7.8	40	40~17	7	390×240×290	21	1168	G1½	G1
CPm190	1.5	2	7.8	48	48~20	7	390×260×320	24.5	981	G1	G1
CPm200	2.2	3	8.4	55	55~20	7	455×280×340	33.5	742	G1	G1

Note: The length of cable is 0.3m, no plug.