

CA



Application Limits

- ⊙ The conveying medium is clean water and other liquids with similar properties to water
- ⊙ Medium temperature range 0°C ~ +90°C (CA1000: 0°C ~ +60°C)
- ⊙ The pH of the medium is between 6.5 and 8.5
- ⊙ The volume ratio of solid impurities is not more than 0.1%, and the particle size is not more than 0.2mm
- ⊙ The voltage is single-phase AC 220V, and the voltage fluctuation range is ±10% of the rated value.

Advantages & Features

- ⊙ Permanent magnet motor
- ⊙ Variable frequency and constant pressure
- ⊙ Simple style
- ⊙ Large touch screen

Performance Data

Model	Power		Max. Flow (m ³ /h)	Max. Head (m)	Head Range (m)	Max. Suction (m)	Packing Dim. L×W×H(mm)	G.W (kg)	20'Loading Qty. (pcs)	Inlet	Outlet
	kW	HP									
CA200	0.2	0.27	3.8	30	25~4	5	275×168×228	5.4	1512	G1	G1
CA600	0.6	0.8	6	45	40~2	6	344.5×188×266.5	7.4	882	G1	G1
CA1000	1	1.36	7.2	50	45~10	6	408×260×205	11.5	595	G1	G1