

XPS



XPS-F



XPS



XPS

#### Application Limits

- Liquid temperature: +2°C ~ +110°C
- Maximum ambient temperature +40°C
- Maximum system pressure 10bar
- Protection level: IP44
- Mains connection: 220V/50Hz
- Insulation class: H
- Pumped liquid characteristics: clean, free from solids and mineral oils, non-toxic, chemically neutral, close to the characteristics of water
- Installation: the motor shaft must be kept in horizontal direction
- pH: 6.5 to 8.5

#### Advantages & Features

- 3-speed adjustment
- Low noise
- No leakage

### Performance Data

Model	Speed	Input Power P1(W)	Current (A)			Capacitor		Pipe Distance (mm)	Max. Head (m)	Head Range (m)	Max. Flow (m <sup>3</sup> /h)	Inter Box		Outer Box		
			220V 50Hz	220V 60Hz	127V 60Hz	μF/450V	μF/250V					G.W. (kg)	Dim. (L×W×H)	PCS/ CTN	Dim. (L×W×H)	G.W. (kg)
						220V 50Hz/60Hz	127V/ 60Hz									
XPS15-4 -130	3	60	0.26	/	/	2	/	130	4	0~4	2	2.5	150x130x140		320x280x300	21
	2	45	0.20	/	/	2	/	130	4	0~4	2	2.5	150x130x140		320x280x300	21
	1	30	0.13	/	/	2	/	130	4	0~4	2	2.5	150x130x140		320x280x300	21
XPS15-6 -130	3	90	0.40	0.40	0.80	2.5	6	130	6	0~6	2	2.5	150x130x140		350x280x300	21
	2	65	0.30	0.30	0.65	2.5	6	130	6	0~6	2	2.5	150x130x140		320x280x300	21
	1	45	0.20	0.20	0.4	2.5	6	130	6	0~6	2	2.5	150x130x140		320x280x300	21
XPS15-9 -140	3	120	0.48	0.48	0.95	3	10	140	9	0~9	1.6	2.8	180x120x135		380x260x290	23
	2	85	0.38	0.38	0.66	3	10	140	9	0~9	1.6	2.8	180x120x135		380x260x290	23
	1	60	0.26	0.26	0.45	3	10	140	9	0~9	1.6	2.8	180x120x135		380x260x290	23
XPS20-4 -130	3	60	0.26	/	/	2	/	130	4	0~4	2.2	2.7	150x130x140		320x280x300	22
	2	45	0.20	/	/	2	/	130	4	0~4	2.2	2.7	150x130x140		320x280x300	22
	1	30	0.13	/	/	2	/	130	4	0~4	2.2	2.7	150x130x140		320x280x300	22
XPS20-6 -130	3	90	0.40	0.40	0.80	2.5	6	130	6	0~6	2.2	2.7	150x130x140		320x280x300	22
	2	65	0.30	0.30	0.65	2.5	6	130	6	0~6	2.2	2.7	150x130x140		320x280x300	22
	1	45	0.20	0.20	0.4	2.5	6	130	6	0~6	2.2	2.7	150x130x140		320x280x300	22
XPS25-4 -130	3	60	0.26	/	/	2	/	130	4	0~4	3	3.0	150x130x140	8	320x280x300	25
	2	45	0.20	/	/	2	/	130	4	0~4	3	3.0	150x130x140		320x280x300	25
	1	30	0.13	/	/	2	/	130	4	0~4	3	3.0	150x130x140		320x280x300	25
XPS25-6 -130	3	90	0.40	0.40	0.80	2.5	6	130	6	0~6	3	3.0	150x130x140		415x280x330	25
	2	65	0.30	0.30	0.65	2.5	6	130	6	0~6	3	3.0	150x130x140		415x280x330	25
	1	45	0.20	0.20	0.4	2.5	6	130	6	0~6	3	3.0	150x130x140		415x280x330	25
XPS25-4 -180	3	60	0.26	/	/	2	/	180	4	0~4	3	3.2	200x130x155		415x280x330	26
	2	45	0.20	/	/	2	/	180	4	0~4	3	3.2	200x130x155		415x280x330	26
	1	30	0.13	/	/	2	/	180	4	0~4	3	3.2	200x130x155		415x280x330	26
XPS25-6 -180	3	90	0.40	0.40	0.80	2.5	6	180	6	0~6	3	3.2	200x130x155		415x280x330	26
	2	65	0.30	0.30	0.65	2.5	6	180	6	0~6	3	3.2	200x130x155		415x280x330	26
	1	45	0.20	0.20	0.4	2.5	6	180	6	0~6	3	3.2	200x130x155		415x280x330	26
XPS32-4 -180	3	60	0.26	/	/	2	/	180	4	0~4	3.5	3.6	200x130x155		415x280x330	30
	2	45	0.20	/	/	2	/	180	4	0~4	3.5	3.6	200x130x155		415x280x330	30
	1	30	0.13	/	/	2	/	180	4	0~4	3.5	3.6	200x130x155		415x280x330	30
XPS32-6 -180	3	90	0.40	0.40	0.80	2.5	6	180	6	0~6	3.5	3.6	200x130x155		415x280x330	30
	2	65	0.30	0.30	0.65	2.5	6	180	6	0~6	3.5	3.6	200x130x155		415x280x330	30
	1	45	0.20	0.20	0.41	2.5	6	180	6	0~6	3.5	3.6	200x130x155		415x280x330	30
XPS20 -12-180	3	245	1.04	1.04	1.80	6	20	180	12	0~12	3	4.8	200x160x180	4	415x340x200	20
	2	210	0.92	0.92	1.60	6	20	180	12	0~12	3	4.8	200x160x180		415x340x200	20
	1	140	0.63	0.63	1.10	6	20	180	12	0~12	3	4.8	200x160x180		415x340x200	20
XPS25-8 -180	3	200	0.83	0.83	1.65	6	15	180	8	0~8	7	5.0	200x160x180		415x340x200	21
	2	185	0.78	0.78	1.55	6	15	180	8	0~8	7	5.0	200x160x180		415x340x200	21
	1	145	0.62	0.62	1.45	6	15	180	8	0~8	7	5.0	200x160x180		415x340x200	21
XPS25 -12-180	3	245	1.04	1.04	1.80	6	20	180	12	0~12	3.5	5.0	200x160x180		415x340x200	21
	2	210	0.92	0.92	1.60	6	20	180	12	0~12	3.5	5.0	200x160x180		415x340x200	21
	1	140	0.63	0.63	1.10	6	20	180	12	0~12	3.5	5.0	200x160x180		415x340x200	21
XPS32-8 -180	3	245	1.04	1.04	1.80	6	/	180	8	0~8	10	5.4	200x160x180		415x340x200	22
	2	210	0.92	0.92	1.60	6	/	180	8	0~8	10	5.4	200x160x180		415x340x200	22
	1	140	0.63	0.63	1.10	6	/	180	8	0~8	10	5.4	200x160x180		415x340x200	22